

Bell 206 Exterior Kit PAGE 1 of 3

NOTE: Modifications and changes to accomodate your specific aircraft will be made at <u>NO EXTRA CHARGE</u>. Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

CARGO TO BE SECURED

MAX ALLOWABLE WEIGHT 250 LBS.
MAX ALLOWABLE WEIGHT PER SQ. FT. 86 LBS.

CARGO TO BE SECURED

MAX ALLOWABLE WEIGHT 250 LBS.
MAX ALLOWABLE WEIGHT PER SQ. FT. 86 LBS.

CAUTION

INLET, EXHAUST, PITOT COVERS, ROTOR TIE DOWN AND BELL FIRST AID KIT MAY BE PLACED IN EXTENSION AREA WITH SNAP COVER INSTALLED. REDUCE MAXIMUM ALLOWABLE BAGGAGE COMPARTMENT WEIGHT 5 POUNDS.

CAUTION

INLET, EXHAUST, PITOT COVERS, ROTOR TIE DOWN AND BELL FIRST AID KIT MAY BE PLACED IN EXTENSION AREA WITH SNAP COVER INSTALLED. REDUCE MAXIMUM ALLOWABLE BAGGAGE COMPARTMENT WEIGHT 5 POUNDS.

BAGGAGE COMPARTMENT RESTRICTED
TO 110 LBS. MAX. WHEN AIRCARFT
LOADED WITH THREE REAR
SEAT PASSENGERS

BAGGAGE COMPARTMENT RESTRICTED
TO 110 LBS. MAX. WHEN AIRCARFT
LOADED WITH THREE REAR
SEAT PASSENGERS

WITH FLIGHT MANUAL INSTRUCTION		OPEN →	FUEL CELL VENT	<u>SE</u>	FOR OPERATING TEMPERATURES BELOW 40° F OAT, FUEL USED MUST CONTAIN PFA-55MB ADDITIVE. CONCENTRATION	
DO NOT USE FOR HANDLING HELICOPTER	OPEN↑ -LOCKED-	CLOSED → VENT	FWD DOOR(S) OFF VNE 80 MPH (69 KNOTS) C.G. 106-110	SERVICE V OIL OR M DO SEE FLI	TO BE .06% - CARGO MUST BE SECURED II ACCORDANCE WITH FLIGHT N	.15% BY VOLUME
DO NOT USE FOR HANDLING HELICOPTER	OPEN† -LOCKED- OPEN†	VENT 28V DC	TURN BATTERY SWITCH ON WHEN USING GROUND POWER	GHI NOT NITH I	MIN. TURB 97% MIN ABOVE 8000 FT. AB BASIC CONFIGURATI VNE 150 N	. Turb 100% Turbe 97% 10% 2000 FT. IRSPEED LIMITATIONS ON 2900 LES GROSS WEIGHT OR LESS PM SEA LEVEL TO 3000 FEET
NO STEP	-LOCKED- OPEN† -LOCKED-	STATIC KEEP (STATIC KEEP (SERVICE WITH MIL-L-7808 OIL OR MIL-L-23699 OIL DO NOT MIX SEE FLIGHT MANUAL SERVICE WITH MIL-L-7808 OIL OR MIL-L-23699 OIL DO NOT MIX SEE FLIGHT MANUAL	-7808 9 OIL IAL	ENGINE DE	DECREASE VICE 4.0 MPH PER 1000 FEET UM ALTITUDE 20,000 FEET CK DRAIN 90 GAL 90 GAL
NO STEP	PITOT DRAIN STATIC DRAIN GROUND HERE	VENTS CLEAN VENTS CLEAN			EXT POWER JET A ONLY N N JET A ONLY	
NO STEP GROUND HERE			PUSH FOR FUEL SUMP DRAIN	FUEL JP CAPACITY FUEL QT FUEL QTY	O O S S T T E E P P	JACK POSITION JACK POSITION
MAXIMUM ALLOWABLE BALLAST 20 POUNDS MAXIMUM ALLOWABLE BALLAST FWD 28 LBS			FUEL CAP 110 U.S. GAL USE ASTM-D-1655 JET A, A-1, AND B.	수 는 그		JACK POSITION 88 GAL 88 GAL
MAXIMUM ALLOWABLE BALLAST 30 POUNDS BALLAST FWD 22 LB		FWD 22 LBS	FUEL CAP 76 U.S. GAL USE ASTM-D-1655 JET A, A-1, AND B.	OR JP-5 O GALLON FULL ADJ EMPTY AD.	NO PUSH NO PUSH	82 GAL 82 GAL 76 GAL 76 GAL
	SOFT	goods only	FUEL CAP 91 U.S. GAL USE ASTM-D-1655 JET A, A-1, AND B	ONS	NO PUSH NO PUSH	GROUND HERE FUEL VENT



Bell 206 Exterior Kit PAGE 2 of 3

PAGE 2 of 3

NOTE: Modifications and changes to accomodate your specific aircraft will be made at NO EXTRA CHARGE.

Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

MAXIMUM ALLOWABLE

BALLAST AFT 9 LBS

MAXIMUM ALLOWABLE

BALLAST AFT 18 LBS

TY 110 GALLONS

FUEL JP-4 OR JP-5 APACITY 110 GALLONS

WARNING: OPENING INSTRUCTIONS

1. OPEN REAR DOOR

2. LIFT HANDLE

3. ROTATE 64° TO OPEN DOOR

CAUTION

CAUTION DO NOT ADD WATER UNLESS BATTERY IS FULLY CHARGED SEE MAINTENANCE MANUAL

CLOSING INSTRUCTIONS

1. CLOSE DOOR

2. ROTATE HANDLE TO CLOSE POSITION

BAGGAGE COMPARTMENT RESTRICTED TO 110 LBS MAX WHEN AIRCRAFT IS LOADED WITH THREE REAR SEAT PASSENGERS WHEN USING RANGE ENTENDER FUEL CAPACITY

MAXIMUM ALLOWABLE WEIGHT PER SQ. FT 86 LBS

STATIC PORT TO RELEASE NO PUSH NO PUSH STATIC PORT TO RELEASE NO PUSH NO PUSH

TURN & PULL TURN & PULL





Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065



Bell 206 Exterior Kit PAGE 3 of 3

PAGE 3 of 3

NOTE: Modifications and changes to accomodate your specific aircraft will be made at NO EXTRA CHARGE.

Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

