


Bell UH-1 Huey Exterior Kit PAGE 1 of 3

NOTE: Modifications and changes to accomodate your specific aircraft will be made at NO EXTRA CHARGE.

Partial kits available upon request.



Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

28V

D.C.

JACK HERE

JACK HERE

JETTISON HANDLE INSIDE

JETTISON HANDLE INSIDE

TAIL ROTOR

SLIDE



Bell UH-1 Huey Exterior Kit PAGE 2 of 3

NOTE: Modifications and changes to accomodate your specific aircraft will be made at <u>NO EXTRA CHARGE</u>.

Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065



SERVICE GEAR BOX WITH
MIL-L-23699 OIL ABOVE -25°F
MIL-L-7808 OIL BELOW -25°F

TRANSMISSION OIL ACCESS DOD-L-85734 ABOVE O F MIL-L-7808 BELOW O F AUX FUEL
L-PUMP SEAL DRAIN
M-SCUPPER SEAL DRAIN
N-CELL DRAIN
O-CELL VENT

AUX FUEL
L-PUMP SEAL DRAIN
M-SCUPPER SEAL DRAIN
N-CELL DRAIN
O-CELL VENT



STRUCTURAL PANEL REQUIRED FOR JACKING, TOWING, HOISTING, GROUND RUN AND FLIGHT.

STRUCTURAL PANEL REQUIRED FOR JACKING, TOWING, HOISTING, GROUND RUN AND FLIGHT.

STRUCTURAL PANEL REQUIRED FOR JACKING, TOWING, HOISTING, GROUND RUN AND FLIGHT.



NO STEP

TRANSMISSION OIL ACCESS
DOD-L-85734 ABOVE 0 F
MIL-L-7808 BELOW 0 F

COWL
LATCH

COWL
LATCH

NO STEP

	MIL-L-7808 BELOW 0 F				LATCH III O	
STEP	ACCESS	FOR FIRE	NO PUSH	NO PUSH	NAV. ELEVANOSE DONN. RIVET P	CROSS TUBE
STEP	EXTINGUISHER		NO PUSH	NO PUSH	FULL AFT CYCLIC STICK RIVET S	MOORING LOAD NOT TO EXCEED FWD
STEP	ACCESS	FOR FIRE	NO PUSH	NO PUSH	FULL FWD CYCLIC STICK RIVET	2600 LBS VERT ON 5000 LBS FORE & AFT
STEP	EXTINGUISHER		NO PUSH	NO PUSH	ENGINE OIL TANK INSIDE	CROSS TUBE
STEP	NO PUSH	NO PUSH	NO STEP	NO STEP	MIL-L-23699 OIL ABOVE - 25°F MIL-L-7808 OIL BELOW - 25°F	NOT TO EXCEED FWD 2600 LBS VERT ON
STEP	NO PUSH	NO PUSH	NO STEP	NO STEP	WILL E 7000 OIL BELOW 201	5000 LBS FORE & AFT
STEP	NO PUSH	NO PUSH	NO STEP	NO STEP	REMOVE TO SERVICE WITH	HAND HOLD
STEP	NO PUSH	NO PUSH	NO STEP	NO STEP	DOD-L-85734 ABOVE O F MIL-L-7808 BELOW O F	HAND HOLD

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065



Bell UH-1 Huey Exterior Kit PAGE 3 of 3

NOTE: Modifications and changes to accomodate your specific aircraft will be made at NO EXTRA CHARGE. Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 Fax: 1-970-461-2065 www.aerographics.com

STA 80 † STA 100 † STA 120 †	FUEL PUMP ACCESS and SUMP DRAIN FUEL PUMP ACCESS and SUMP DRAIN	TIE DOWN RING MOORING LOAD ON RING NOT TO EXCEED 1000 LBS VERTICALLY 500 LBS LATERALLY 500 LBS FWD/AFT
STA 140 † STA 160 †		TIE DOWN RING
SIA 160 1		MOORING LOAD ON RING NOT TO EXCEED
	HYDRAULIC RESERVOIR INSIDE	1000 LBS VERTICALLY 500 LBS LATERALLY
	WHEN FLUID LEVEL IS VISIBLE	500 LBS FWD/AFT
STA 80 t	FILL TO OVERFLOW	TIE DOWN DING
STA 100 1 STA 120 1		TIE DOWN RING MOORING LOAD ON RING NOT TO EXCEED 1000 LBS VERTICALLY 500 LBS LATERALLY
STA 140 † STA 160 †	CLOSE THIS CLOSE THIS COWL FIRST COWL FIRST	500 LBS FWD/AFT

TIE DOWN RING MOORING LOAD ON RING NOT TO EXCEED 1000 LBS VERTICALLY 500 LBS LATERALLY 500 LBS FWD/AFT

FUEL CELL CAVITY DRAIN & VENT

BATTERY VENT

CROSS TUBE MOORING LOAD NOT TO EXCEED AFT 3500 LBS VERT ON

CROSS TUBE MOORING LOAD 3500 LBS VERT ON 5000 LBS FORE & AFT

FUEL CELL CAVITY OIL TANK VENT **DRAIN & VENT**

5000 LBS FORE & AFT CAP. 209 U.S. GAL.

USE MIL-T-5624 GRADE JP-8 IF NOT AVAILABLE REFER TO

FUEL CELL DRAIN BATTERY VENT TB 55-9150-200-24 FOR **ALTERNATE FUEL**

FUEL CELL DRAIN

HEATER DRAIN

BATTERY ACCESS

HAND FIRE **EXTINGUISHER INSIDE**



RADIO ACCESS

BATTERY VENT

BATTERY VENT

CAP. 209 U.S. GAL.

USE MIL-T-5624 GRADE JP-4

IF NOT AVAILABLE REFER TO

TB 55-9150-200-24 FOR ALTERNATE FUEL

HYD PUMP DRAIN



www.aerographics.com Phone: 1-800-336-9633 Fax: 1-970-461-2065