



Cessna 421 Exterior Kit PAGE 1 of 2

NOTE: Modifications and changes to accommodate your specific aircraft will be made at **NO EXTRA CHARGE.**
Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633

www.aerographics.com

Fax: 1-970-461-2065

AVGAS ONLY GRADE 100 	20 US GAL	AVGAS ONLY GRADE 100 	AVGAS ONLY GRADE 100LL 
AVGAS ONLY GRADE 100 	20 US GAL	AVGAS ONLY GRADE 100 	AVGAS ONLY GRADE 100LL 
AVGAS ONLY GRADE 100 	20 US GAL	AVGAS ONLY GRADE 100 	AVGAS ONLY GRADE 100LL 
TANK & SUMP TANK & SUMP DRAINS DRAINS			
TANK & SUMP TANK & SUMP DRAINS DRAINS			
TANK & SUMP TANK & SUMP DRAINS DRAINS			
TANK & SUMP TANK & SUMP DRAINS DRAINS			
TANK & SUMP TANK & SUMP DRAINS DRAINS			
TANK & SUMP TANK & SUMP DRAINS DRAINS			
GROUND POINT GROUND POINT GROUND POINT GROUND POINT			

IF WATER IS OBSERVED AT THE FUEL STRAINER, FUEL TANK SUMPS MUST BE DRAINED

NOTICE
IF WATER IS OBSERVED AT THE FUEL STRAINER, FUEL TANK SUMPS MUST BE DRAINED

NO PUSH CROSSFEED LINE DRAIN ONLY	NO PUSH CROSSFEED LINE DRAIN ONLY	NO PUSH STATIC SOURCE DRAIN
NO PUSH FUEL FILTER LOCATOR BEACON DRAIN DAILY	NO PUSH FUEL FILTER LOCATOR BEACON DRAIN DAILY	NO PUSH JACK PAD JACK PAD JACK PAD
NO PUSH FUEL FILTER LOCATOR BEACON DRAIN DAILY	NO PUSH FUEL FILTER LOCATOR BEACON DRAIN DAILY	NO PUSH 50 US GAL
NO PUSH OIL FILL 12 QTS	NO PUSH OIL FILL 12 QTS	NO PUSH OIL FILL 12 QTS
NO PUSH OIL FILL 12 QTS	NO PUSH OIL FILL 12 QTS	NO PUSH OIL FILL 12 QTS
NO PUSH MAIN GEAR FILLING/SERVICE SEE P.O.H.	NO PUSH MAIN GEAR FILLING/SERVICE SEE P.O.H.	NO PUSH LEVEL POINT
NO PUSH STATIC SOURCE KEEP CLEAN	NO PUSH ENG OIL FILL	NO PUSH STATIC VENTS KEEP CLEAR
NO PUSH FUEL STRAINER DRAIN DAILY	NO PUSH ENG OIL FILL	NO PUSH STATIC VENTS KEEP CLEAR
NO PUSH FUEL STRAINER DRAIN DAILY	NO PUSH ENG OIL FILL	NO PUSH STATIC VENTS KEEP CLEAR
NO PUSH ENG OIL FILL	NO PUSH ENG OIL FILL	NO PUSH STATIC VENTS KEEP CLEAR

NO PUSH NO PUSH NO PUSH
NO PUSH NO PUSH NO PUSH
NO PUSH NO PUSH NO PUSH
NO PUSH NO PUSH NO PUSH

STATIC SOURCE DRAIN
JACK PAD JACK PAD JACK PAD
50 US GAL
NOSE GEAR FILLING/SERVICE SEE P.O.H.
OXYGEN HIGH PRESSURE RELIEF DO NOT COVER
FUEL STRAINER DRAIN DAILY
FUEL STRAINER DRAIN DAILY
OPERATION TO OPEN DOOR
ROTATE HANDLE TO CLOSE
ROTATE HANDLE TO OPEN

FUEL TRANSFER 100/130 AVIATION GRADE MIN. USABLE 28 GAL

FUEL TRANSFER 100/130 AVIATION GRADE MIN. USABLE 28 GAL

FUEL TRANSFER 100/130 AVIATION GRADE MIN. USABLE 28 GAL

FUEL TRANSFER 100/130 AVIATION GRADE MIN. USABLE 28 GAL

AUX FUEL 100-130 AVIATION GRADE MIN. USABLE 48 GAL

AUX FUEL 100-130 AVIATION GRADE MIN. USABLE 48 GAL

FUEL 100/130 AVIATION GRADE MIN. USABLE 103 GAL

FUEL 100/130 AVIATION GRADE MIN. USABLE 103 GAL

FLUX VALVE
USE NON MAGNETIC TOOLS & SCREWS

RUDDER LOCK

ANTI-COLLISION LIGHT REG. FOR PROPER MASS BALANCE DO NOT REMOVE

TRANSFER LINE DRAIN DRAIN DAILY

AUX FUEL 100-130 AVIATION GRADE MIN. USABLE 48 GAL

100-130 AVIATION GRADE MIN. USABLE 48 GAL

TO OPEN DOOR ROTATE HANDLE DOWN DEPLOY UPPER DOOR ROTATE SILL LEVER UP STAND CLEAR AND DEPLOY LOWER DOOR

ANTI-COLLISION LIGHT REG. FOR PROPER MASS BALANCE DO NOT REMOVE

FLUX VALVE

FUEL 100/130 AVIATION GRADE MIN. USABLE 103 GAL

FUEL 100/130 AVIATION GRADE MIN. USABLE 103 GAL

AUX FUEL 100-130 AVIATION GRADE MIN. USABLE 48 GAL

FUEL 100/130 AVIATION GRADE MIN. USABLE 103 GAL

AeroGraphics

The Original Aircraft Lettering Company



Cessna 421 Exterior Kit PAGE 2 of 2

NOTE: Modifications and changes to accommodate your specific aircraft will be made at NO EXTRA CHARGE.
Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

SECURE PRIOR TO FLIGHT	SECURE PRIOR TO FLIGHT	A/C HYDRAULIC MOORING GROUND PUSH AFT
SECURE PRIOR TO FLIGHT	SECURE PRIOR TO FLIGHT	MOORING GROUND PUSH AFT
SECURE PRIOR TO FLIGHT	SECURE PRIOR TO FLIGHT	DISARM SWITCH
SECURE PRIOR TO FLIGHT	SECURE PRIOR TO FLIGHT	OPEN
28 U.S. GAL USABLE	28 U.S. GAL USABLE	LOCK 28 GAL
EXTERNAL POWER 24 VOLTS D.C.	EXTERNAL HYD RESERVOIR FILL MIL - H - 5606	EXTERNAL HYD RESERVOIR FILL MIL - H - 5606
BATTERY SWITCH OFF WHEN NOT IN USE		
EXTERNAL POWER 24 VOLTS D.C.		
BATTERY SWITCH OFF WHEN NOT IN USE		
ALCOHOL ANTI-ICE ISO - ALC MIL - F - 5566		
CAPACITY 3.0 GAL.		
PLACE LEVEL BETWEEN MARKS FOR LATERAL LEVELING		
OXYGEN FILLER AVIATORS BREATHING OXYGEN PER MIL - 0 - 27210		
SEE SERVICE MANUAL FOR SERVICE INSTRUCTIONS		

EXTERNAL POWER 24 VOLTS D.C.

TO CLOSE LOWER DOOR
STOW LOWER DOOR ROTATE SILL LEVER DOWN TO LOCK
TO LOCK UPPER DOOR
ROTATE HANDLE UP TO LOCK
STOW HANDLE

EMERGENCY EXIT

CAUTION
WHEN REMOVING OXYGEN BOTTLE CAP LINE FITTING WITH PLASTIC CAP

NO STEP

NO STEP

TOW LIMITS

NO PUSH

DISENGAGE RUDDER & CONTROL LOCKS BEFORE GROUND HANDLING

NO PUSH


NO PUSH

UNLOCK  **LOCK**
UNLOCK
BEFORE TAXI AND FLIGHT

NO PUSH

NO PUSH

NO PUSH



TEST AND EMERGENCY

TURN  **LIMITS**

DISENGAGE RUDDER & CONTROL LOCKS BEFORE GROUND HANDLING

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065